PELLE CURTESOFT WP-ES

CHARACTERISTIC

Special Fats

Chemical structure	**:**	Greasing fat polymer
Apperance	**:**	Viscous liquid
Colour:	**:**	White, opalescent
Concentration (%)	**:**	51±2
pH	**:**	6,5±0,5
Charge	**:**	Anionic

PROPERTIES AND APPLICATION

– Several special fatliquors range for special applications/articles.

– Having diverse chemical composition.

– Waterproofing fatliquor. Medium level. Recommended for soft articles, like gloves, garments, nappa. It can be used as a single fat.

– Waterproofing Application: It is recommended not to use any surfactant during the process and a make strong neutralisation, not lower than pH 4,8. The maximum effect is achieved after fixation of fat at the end of process with a metallic salt (Cr, Al, Zr).

"TOUCH WITH PELLECURTEX"

- – It can be used like a touching agent.

- – Guidance Dosages: General waterproofing (% on shaved weight):

  - After neutralization prior to retanning: 3-8%

  - In fresh fatliquor bath: 5-10 %

  - As a touching agent together or after fatliquoring: 0,5-2 %.

STORAGE

In a cool and dry place in original packaging, can be stored for a period of one year. Product must be protected from excessive heat and cold.

PACKAGING

Bulk in 120 kg polyethylene drums.

"TOUCH WITH PELLECURTEX"