



PELLE CURTEBASE SP 2030

CHARACTERISTIC

Water based pre bottom

Appearance : White viscous liquid

Concentration (%) : 21±1

pH : 8,0-9,0

Charge : Anionic

PROPERTIES AND APPLICATION

- *PELLECURTEBASE SP 2030* is modified water based acrylic and polyurethane polymers dispersion.
- This product is a water based pre-bottom, developed to reduce the size of the pores and to level small defects of the leather, allowing to obtain very soft and natural finished leathers.
- *PELLECURTEBASE SP 2030* is mainly developed for full grain leathers, but it can be applied also on slightly buffed articles. Once applied by roller coater, it does not need to be buffed and felter polished; it shows good adhesion with the various finishing layers and it can be directly embossed or drymilled. Before dry-milling and embossing it is suggested to spray a nitroemulsion of our *PELLECURTELAC* series.
- The product is applied by roller-coater in quantity ranging between 2-4 gr/sqft. During application it can be mixed with pigments in percentages of 10-15% without affecting its technical and rheological properties.
- It is recommended to stir the product before use, to protect against frost and to store in tightly sealed original containers.

STORAGE

In a cool and dry place in original packaging, can be stored for a period of one year. Product must be protected from excessive heat and cold.

PACKAGING

Bulk in 60-120 kg drums.

”TOUCH WITH PELLECURTEX”

Technical information and recommendations contained herein, is reliable, but conditions and methods of use of our products are beyond our control not imply any warranty. We recommend to use to our customer after identified our products and the suitability of proposals of use. Tips on the use of our products be interpreted in terms of encouraging infringement of patent rights of others.