



March 2017

PELLE CURTESOFT AK

CHARACTERISTIC

Full Synthetic and Sulfated Oil

Chemical Structure	: Mixture of synthetic and sulfated oil
Appearance	: Brownish, viscous liquid
Concentration (%)	: $70,0 \pm 1,0$
pH (10 % in water)	: 6,0 - 7,0
Ionic Structure	: Anionic

PROPERTIES AND APPLICATION

PELLE CURTESOFT AK is used in main fatliquoring and suitable for all kinds of leather especially garment, suede, bovine and glove leather.

It is used in combination in the fatliquor bath.

It gives soft and grain tight leathers with a remarkable greasy touch.

It is stable to hard water and acids used in fatliquoring.

It provides surface and sufficient inner fatliquoring.

It is recommended to use in concentration of 3,0 – 6,0 % together with other fatliquoring agent.

STORAGE

In a cool and dry place in original packaging, can be stored for a period of one year. Product must be protected from excessive heat and cold.

PACKAGING

120 kg drums.

“TOUCH WITH PELLECURTEX”

Technical information and recommendations contained herein, is reliable, but conditions and methods of use of our products are beyond our control not imply any warranty. We recommend to use to our customer after identified our products and the suitability of proposals of use. Tips on the use of our products be interpreted in terms of encouraging infringement of patent rights of others.